

## DESCRIPTION OF CORNER EVIDENCE FOUND

USED SINGLE PROPORTIONATE MEASUREMENT METHOD TO DETERMINE THE EAST—WEST POSITION OF CORNER WHICH SEEMED TO MATCH VERY NEARLY WITH THE ROAD RIGHT—OF—WAY OCCUPATION PROJECTED FROM THE NORTH. ALSO USED THE EXISTING MONUMENTS AND FENCE LINES TO THE NORTH AND SOUTH TO DETERMINE THE NORTH—SOUTH POSITION OF THE CORNER.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

SET 5/8"X24" REBAR WITH CAP AT SECTION CORNER

(REFERENCED AS SHOWN)

STATE PLANE COORDINATE DATA

## CERTIFICATION

I <u>Jerry D. Allred</u>, Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date 12 Dec 2005

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

SCANNED 12 DEC

2005

